Drainage Agreement Details



This check list shall be used to guide the user through the activities required to meet "asconstructed" specifications defined within Melbourne Water Survey as per the Land Development Website.

Job Title:		
Municipality:		
Developer:		
Consultant:		
Nominated Rep.:		
Consultant Ref.:		
Melbourne Water Ref.:	EPMS/	
Recording of "A	As-Constructed" Detail	
1.	General	Initials
1.1.	All documentation has been adequately labelled with drain numbers and name and section number of works as per the Works Offer	
1.2.	Date of construction completion has been noted	
1.3.	The original design plans have been annotated and updated to "As Constructed"	
1.4.	Addendum plans have been created due to constructed works being significantly different to design	
1.5.	Addendum plans have been created due to inability to annotate the original design plans	
1.6.	Addendum plan numbers have been agreed to by Melbourne Water	
1.7.	All Manholes have unique numbers	
1.8.	Sheets containing "as-constructed" data have been certified and signed by a licensed surveyor or VeriSign for electronic documents	
1.9.	All constructed works that are not in accordance with design have been appropriately noted (i.e. new alignments, different materials, structural	



		sizes)	
	1.10.	Submission to consist of only digital files where PDFs are certified using Verisign digital security technology (Signed A1 hardcopy accompanied by digital data as per Section 10 of this Checklist may be provided if digital signature services are not available)	
	1.11.	Each drawing shall be in a separate pdf file and oriented to landscape layout	
2.		Offset, Ties and MGA co-ordinates	
	2.1.	All the centrelines of underground pipelines, open channels and levee banks have been appropriately recorded in relation to title	
	2.2.	MGA co-ordinates have been provided where the subdivision was duly co-ordinated	
	2.3.	MGA co-ordinates have been determined for appropriate title corners	
	2.4.	Manhole and structures have been appropriately related to title	
	2.5.	Datum for co-ordinates have been annotated on the design plans	
3.		Longitudinal Section	
	3.1.	The longitudinal section has been annotated with invert levels and running chainages	
	3.2.	Invert levels have been taken at tangent points, inlets and outlets of structures, start and end transitions, changes of grade, fittings (including manholes) and any aprons	
	3.3.	Running chainages have been established for each of the invert levels	
	3.4.	Pipe and/or channel grades have been recomputed and updated where significantly different to design by 15% or greater.	
	3.5.	Datum points for establishing AHD have been annotated on the design plan	
4.		Cross Sections	



	4.1.	Cross-sections have been annotated with levels	
		and offsets	
	4.2.	Cross-sections show the relationship to title where appropriate	
	4.3.	Each of the cross-sections has been identified with a running chainage	
	4.4.	The "as-constructed" cross-sections have been superimposed over the design cross sections where there is significant difference	
	4.5.	Cross-sections show applicable 1 in 100 ARI flood level	
5.		Structural Details	
	5.1.	The cover levels of each structure have been annotated on the structural schedule	
	5.2.	The structural schedule has been updated with	
		inlet and outlet inverts	
	5.3.	Detailed inserts have been updated with dimensions where significantly different to design	
6.		Sizes, Materials and Stubs	
	6.1.	The structure schedule has been updated withinlet and outlet pipe sizes	
	6.2.	Where the constructed Works have been built with different materials, these has been noted on the design plans	
	6.3.	Invert levels have been established for both ends of the stub pipe	
	6.4.	The direction of the stub has been determined	
7.		Feature Plans	
	7.1.	Spot Levels have been annotated on the design plans	
	7.2.	Where separate feature plans have been prepared, they contain spot levels and generated contours	



	7.3.	Features such as edges of lakes and Normal Water Level have been delineated	
	7.4.	A condensed long section is provided where required depicting major roads, major obstacles, major topographical features, river/creek crossings.	
	7.5.	A limited amount of text is provided to assist with interpretation, such as manhole numbers, descriptions of unusual features, or road names. Line strings may be used to identify the location of 'as constructed' cross sections	
	7.6.	1 in 100 ARI flood levels and extents for wetlands, retarding basins and waterways	
8.		Lakes, retarding basins and wetlands	
	8.1.	All water bodies and embankments are clearly shown	
	8.2.	Spot levels and generated contours where appropriate (i.e. spot levels may be more appropriate than cross sections)	
	8.3.	"As Constructed" Normal Top Water Level (NTWL) must be labelled and delineated	
	8.4.	A 350 mm or 400 mm contour below NTWL must be labelled and delineated	
	8.5.	Reduce Level (RL) for NTWL and Extended Detention Depth (EDD) must be labelled and delineated	
	8.6.	Planting 'zones' – typically these would be 'ephemeral marsh', 'shallow marsh', 'deep marsh' and 'submerged marsh' (or some similar nomenclature), open water	
	8.7.	Pit details (including oriface control, removable plate, debris guard, riser pipe etc.)	
	8.8.	Link to provided MUSIC model/functional design report	
	8.9.	Catchment size and shape (may be linked to MUSIC model)	
9.		Sediment Ponds	
	9.1.	"As Constructed" Normal Top Water Level (NTWL) must be labelled and delineated	



	9.2.	A 500 mm contour (below NTWL)	
	9.3.	Base of pond (BOP)	
	9.4.	If BOP is 'hard' (rock)	
	9.5.	The designated sediment drying area	
	9.6.	Catchment size specified	
10.		Digital Data	
	10.1.	Digital data has been supplied	
	10.2.	File names are in accordance with the Melbourne Water Planning and Building website	
	10.3.	Digital Data includes the relationship to title boundaries	
	10.4.	CAD files shall be delivered in a single package such as a zip file and contain all reference and system files	
	10.5.	Supplied data is submitted electronically via email, file transfer weblink, a formatted CD or memory stick	